



AVAILABLE BRACKETS	
DESCRIPTION	P/N
LOW PROFILE PCI	SHM-2620-2
STANDARD PCI	SHM-2630-2
CENTRONICS	SHM-2610-2

- PCB DIMENSIONS CONFORM TO PCI LOCAL BUS SPECIFICATION REV 2.2 (LOW PROFILE).
- UNUSED COMPONENT HOLES AND VIAS MAY BE SOLDER FILLED.
- MAX. LEAD TRIM LENGTH IS .060".
- ASSEMBLE IN ACCORDANCE WITH IPC-610A, CLASS 2 (CURRENT REVISION).

NOTES: UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED:	DRAWN	NAME	DATE
DIMENSIONS ARE IN INCHES	DD	DD	12/12/06
TOLERANCES:	CHECKED		
FRACTIONAL ±	ENG APPR.		
ANGULAR: MACH ± BEND ±	MFG APPR.		
TWO PLACE DECIMAL ±	Q.A.		
THREE PLACE DECIMAL ±	COMMENTS:		
INTERPRET GEOMETRIC TOLERANCING PER:			
MATERIAL			
FINISH			
USED ON			
APPLICATION			
DO NOT SCALE DRAWING			

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF <INSERT COMPANY NAME HERE>. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF <INSERT COMPANY NAME HERE> IS PROHIBITED.	
TITLE: iSAS Dual 26-Ckt External 36-Ckt Internal	SIZE DWG. NO. A ADP-8873-2
SCALE: 1:1	SHEET 1 OF 1