



- 2. USE MINIMUM BEND RADIUS.
- 1. DEBURR AND BREAK ALL SHARP EDGES AND CORNERS.

NOTES: UNLESS OTHERWISE SPECIFIED

PROPRIETARY AND CONFIDENTIAL			DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ±1 TWO PLACE DECIMAL ±.010 THREE PLACE DECIMAL ±.005	NAME	DATE	Centronics Bracket Dual iSAS	
				DRAWN	IDS		11/16/06
				CHECKED			
				ENG APPR.			
			MATERIAL				
			.036 THK CRS				
			FINISH				
	NEXT ASSY	USED ON	BRIGHT NICKEL	COMMENTS:			
	APPLICATION		DO NOT SCALE DRAWING				
				Q.A.			
				SIZE A DWG. NO. SHM-2610-2		REV. NC	
				SCALE:1:1	WEIGHT:	SHEET 1 OF 1	

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CS ELECTRONICS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CS ELECTRONICS IS PROHIBITED.